

Calibration Certificate



Cal Cert ID: 239331

Cust. Name: WASHINGTON STATE PATROL

Address: 222 TUMWATER BOULEVARD SOUTHWEST

City: Tumwater

State/Zip: WA

98501

USA

Instr SN: 410004SY/651314

Out1 Min Range:

8.0000 psi

Cal Date: 12/14/2023

Page 1 of 2

Instr Descr: CPG2400

Out1 Max Range:

17.0000 psi

Cal Time: 6:09 pm

Sensor SN: 410004SY/651314

Limit of Error: 0.030% R √

Issue Date: 12/14/2023

Cal Tech: KORBYNR

Sensor Descr: Silicon Pressure Transducer

Procedure ID: WI02063

Pressure Type:

Absolute

Order Nbr: 52855

Test Points Values and Readings \

Test Point	Reference Value	Measured Values	Error	Uncertainty	
#	psi	psi	% R	psi	
1	8.00067	8.0006	-0.0004	1.9E-4	
2	9.80053	9.8009	0.0040	2.2E-4	
2 3	11.60039	11.6011	0.0062	2.6E-4	
4	13.40024	13.4011	0.0062	3.0E-4	
5	15.20015	15.2011	0.0065	3.4E-4	
6	17.00013	17.0012	0.0062	3.8E-4	
7	15.20019	15.2012	0.0063	3.4E-4	
8	13.40026	13.4011	0.0064	3.0E-4	
9	11.60033	11.6010	0.0062	2.6E-4	
10	9.80048	9.8009	0.0047	2.2E-4	
11	8.00060	8.0006	0.0006	1.9E-4	

Measurement Standards Used in Calibration

Std Type	Serial Number	Description	Assoc. Test Reports	Recal Date	
Std Type		The state of the s	CAL ID: 205428	12/14/2024	
CPD8000	10017/10016/9994	DH CPD 8000	CAL ID: 205426	12/14/2024	

The combined and expanded uncertainty is reported at K=2 providing an approximate 95% confidence level.

Remarks and Notes

As Found Calibration.

As Left Calibration.

Recalibration Date:12/14/2024

The standards and calibration program at Mensor complies with the requirements of ISO/IEC 17025:2017, ANSI/NCSL Z540-1 and Mensor Management Manual MM 3.0, Revision D, dated September 21, 2021.

Metrological traceability is established through accreditation by the American Association for Laboratory Accreditation (A2LA), a signatory subject to the International Laboratory Accreditation Cooperation (ILAC) Arrangement as described in Annex A of ISO 17025:2017. All calibrations are performed in ambient conditions of 23 +/- 4 deg C and 20-80% relative humidity.

The results reported herein relate only to the item calibrated. This calibration certificate shall not be reproduced, except in full, without the written approval of Mensor.

Transducer was calibrated in a horizontal position.

THE PRECISION PRESSURE COMPANY

201 BARNES DR. · SAN MARCOS, TEXAS 78666 · 512.396.4200 · FAX 512.396.1820 · WWW.MENSOR.COM



Cal Cert ID:

239331

Page 2 of 2

I, Korbyn Richmond, certify the accuracy of this Calibration Certificate:

Calibration Lab Technician

Mensor Calibration Certificates and Stickers

Mensor calibration certificates and stickers do not contain calibration intervals unless specified by the customer, as Mensor will not dictate to our customers when they should re-calibrate their instruments.

The Calibration Sticker that is with this product is for your records. Due to the various location requirements of our customers, we do not affix the Calibration Sticker to the product.

For Mensor products, refer to the Calibration Section of your operation manual for the recommended calibration interval.